

## IDEM - NON-CONTACT RFID SPF SWITCHES

405001  
SPF-U-RFID 2M



- Switching range - 14 mm
- RFID - coding
- No dedicated controller
- LED indicator
- Compact dimensions



### Product description

### Specifications

<b>Approvals</b>	ISO 13849-1, ISO 14119, EN60204-1, EN62061, EN60947-5-3, UL 508
<b>Cable length</b>	2
<b>Cable type</b>	PVC 6 or 8 core 6mm OD conductors a 0.25 <sup>2</sup>
<b>Coding</b>	Uniquely coded
<b>Conductor size</b>	0,25
<b>Contact rating max</b>	24Vdc 0.2A
<b>Contact Type</b>	2NC safety outputs shorts circuit protected, 1NO auxiliary output for indication of door open
<b>Contacts</b>	2NC 1NO
<b>IP Class</b>	IP67, IP69K
<b>Mechanical reliability B10d</b>	No mechanical parts implemented
<b>Mounting</b>	2 x M4
<b>MTTFd</b>	1100a
<b>Operating temperature</b>	-25°C ... +80°C

<b>PL</b>	e acc. ISO13849-1
<b>Recommended mounting gap</b>	5
<b>Safety category</b>	4
<b>SIL</b>	3 acc. IEC62061
<b>Switching current min</b>	10Vdc 1mA
<b>Switching distance</b>	Sao 10mm close, Sar 20mm open
<b>Switching frequency max</b>	1.0Hz maximum

