



IDEM - NON-CONTACT RFID LMF-SS SWITCHES

406002
LMF Unique 5M

- Switching range - 14 mm
- RFID - coding
- No dedicated controller
- LED indicator
- Stainless steel housing



Product description

Non-contact RFID switch LMF-SS made of stainless steel with a narrow and flat profile and high tolerance, which is ideally suited for applications in the food industry. The switch is resistant to pressure washing.

The LMF-SS switch with RFID has 2NC 1NO semiconductor outputs.

Specifications

Approvals	ISO 13849-1, EN60947-5-3, ISO 14119, EN60204-1, EN62061, UL 508
Cable length	5
Cable type	PVC 6 or 8 core 6mm OD conductors 0.25mm ²
Coding	Uniquely coded
Conductor size	0,25
Contact rating max	24Vdc 0.2A
Contacts	2NC 1NO
IP Class	IP69K, IP67
Mechanical reliability B10d	No mechanical parts implemented
Mounting	2 x M4
MTTFd	1100a
Number of poles	8

Operating temperature	-25°C ... +80°C
PL	e acc. ISO13849-1
Recommended mounting gap	5
Safety category	4
SIL	3 acc. IEC62061
Switching current min	10Vdc 1mA
Switching distance	Sao 8mm close, Sar 20mm open
Switching frequency max	1.0Hz maximum
Weight	435

