
VALCO - LEVEL SWITCH, SIDE MOUNT - B77 SERIES

00.0002.6735 Adj. length, Elbow rod, Brass/SS/ABS, 1xCO, Max 10



senseca

- PP housing with PG9 electrical connection
- Micro-switch SPDT
- Max working pressure 20 bar
- Max working temperature 120°C
- Process connection Brass or St. Steel materials

Product description

These level switches, with their reduced dimensions and simplicity of installation, constitute a reliable solution for the control of liquids in all applications where it is necessary to mount a lateral type. Suitable for use with process temperatures up to 120 ° C

Specifications

Current	3A
Electrical connection	PG9 cable gland
Function	Changeover (SPDT)
Hysteresis Max	24
IP Class	IP65
Manufacturer Part No	L1.B77.7.C.25.G.O.W.I33
Material of body	Glass fiber reinforced plastic (PBT)
Material of float	SPANSIL
Material of seals	PTFE
Materials Wetted Parts	Stainless steel
Max. pressure	Stainless steel 10
Max. pressure	10
Max. pressure Mounting	10 Horizontal
Max. pressure Mounting Number Of Microswitches	10 Horizontal 1
Max. pressure Mounting Number Of Microswitches Process connection	10 Horizontal 1 G1
Max. pressure Mounting Number Of Microswitches Process connection Rod type	10 Horizontal 1 G1 Angled

