

## TECNOPLASTIC - FLOAT SWITCH - OLYMPIC 03

GOAH3G110GNB1

Olympic 03,H07 RNF 3G1,5m,1 func,Bambo

- Maximum depth of 20 metres
- 20° Activation Angle
- Bamboo Arm Included
- Up to 50°C



### Product description

This float switch has an activation angle of 20° for overflow alarm. Constructed with materials very resistant to mechanical stress, it's ideal for applications in turbulent waters as it can help prevent the cable from tangling up so the float can work properly. This can be fitted to wells and tanks with screws (not supplied) or to pipping on pumps of any diameter using the cable ties which are supplied. Assembled with right (recommended) or left orientation, the float switch can be installed in 3 different positions horizontal, vertical, and vertical 180° to allow the regulation of small changes in minimum and maximum level. This can be used in narrow spaces, sewage, and industrial waters.

### Specifications

<b>Approvals</b>	CE, EAC, TÜV
<b>Cable type</b>	H07RN-F
<b>Contact Angle</b>	20
<b>Depth-Max</b>	10
<b>Insulation class</b>	I
<b>IP Class</b>	IP68
<b>Material of float</b>	Polypropylene
<b>Operating temperature to</b>	50
<b>Rated Current</b>	10
<b>Supply Voltage</b>	250



