



## SUCO - 0196/0197 PRESSURE SWITCH

Stainless steel body

0196457031003

0,5..5 bar, G1/4, CO, NBR, Spade, Stainless steel

- Up to 24 V
- Spade terminals
- Five adjustment ranges from 0,5..5 bar to 50..200 bar
- Changeover (SPDT) with gold contacts
- Over pressure safety of 300 bar up to 600 bar



### Product description

The 0196/0197 series is a compact pressure switch and is part of the changeover contact range from SUCO. Offering a maximum voltage of 24 V (gold contacts) with a normally open and normally closed contact housed in a hex 27 stainless steel body offering offering a high pressure resistance. The switch point is very stable even after a long period of time and high load and is also adjustable on site and can come pre-set.

Common applications include power packs and mobile hydraulics

### Specifications

<b>Adjustment range max</b>	5
<b>Adjustment range min</b>	0,5
<b>Approvals</b>	CSA US, RoHS II
<b>Contact load max ac</b>	4
<b>Contact load max dc</b>	0,25
<b>Deviation max</b>	±0,3
<b>Hysteresis</b>	10-30% depending on set value
<b>IP Class</b>	IP00
<b>Lifespan Mechanical</b>	1 million exchanges
<b>Max switching frequency/min</b>	200
<b>Max. pressure</b>	300
<b>Temperature ambient from</b>	-20

Temperature ambient to	80
Temperature range of media from	-40
Temperature range of media to	100
Weight	100
Voltage AC / DC Max	250
Voltage AC / DC Min	10

