



## SUCO - 0240/0241 PRESSURE SWITCH

Pre-cabled (2m)

0240457031003

0,3..1,5 bar, G1/4, CO, NBR, 2M cable

- Up to 250 V depending on connection
- Pre-cabled at 2 metres
- Five adjustable ranges from 0,3..1,5 bar to 50..150 bar
- Changeover (SPDT)
- Over pressure safety of 300 bar or 600 bar



### Product description

The 0240/0241 series is a pre-cabled (2 meters) pressure switch and is part of the changeover contact range from SUCO. Offering a maximum voltage of 42 V or 250 V (depending on connection) with a normally open and normally closed contact housed in a hex 27 zinc plated body offering a high pressure resistance. The switch point is very stable even after a long period of time and high load and is also adjustable on site and can come pre-set.

Common applications include commercial vehicles, mobile hydraulics, excavators etc

### Specifications

<b>Adjustment range max</b>	1,5
<b>Adjustment range min</b>	0,3
<b>Approvals</b>	RoHS II, CE
<b>Contact Rating Max</b>	2
<b>Deviation max</b>	±0.2
<b>IP Class</b>	IP67
<b>Max switching frequency/min</b>	200
<b>Max. pressure</b>	300
<b>Temperature ambient from</b>	-20
<b>Temperature ambient to</b>	80
<b>Temperature range of media from</b>	-40
<b>Temperature range of media to</b>	100
<b>Weight</b>	120

