



## SUCO 0184/0185 PRESSURE SWITCH STAINLESS STEEL

Stainless steel body

0184457031486  
0,5..5 bar, G1/4, CO, NBR, DIN, Stainless steel

- Up to 250 V
- Connector included (DIN 43650/Form A)
- Five adjustment ranges from 0,5..5 bar to 50..200 bar
- Changeover (SPDT)
- Over pressure safety of 300 bar or 600 bar



### Product description

The 0184/0185 series is part of the changeover contact range from SUCO with an integrated plastic body and connector. Offering a maximum voltage of 250 V with a normally open and normally closed contact housed in a hex 27 stainless steel body offering a high pressure resistance. The switch point is very stable even after a long period of time and high load and is also adjustable on site and can come pre-set.

Common applications include power packs, mobile hydraulics, water systems, hydraulics generally and pneumatics.

### Specifications

<b>Adjustment range max</b>	5
<b>Adjustment range min</b>	0,5
<b>Approvals</b>	CSA US, RoHS II
<b>Contact load max ac</b>	4
<b>Contact load max dc</b>	0,25
<b>Deviation max</b>	±0,2
<b>IP Class</b>	IP65
<b>Max switching frequency/min</b>	200
<b>Max. pressure</b>	300
<b>Temperature ambient from</b>	-20
<b>Temperature ambient to</b>	80
<b>Temperature range of media from</b>	-30
<b>Temperature range of media to</b>	100

Weight 130

Voltage AC / DC Max 250

Voltage AC / DC Min 10

