



## SUCO - 0500/0501 ELECTRONIC PRESSURE SWITCH

Factory set

0500200411002

0..2 bar, G1/4, No, PNP, NBR, M12

- Single switch point
- Small & compact
- Ceramic sensor
- Stainless steel housing

### Product description

The SUCO 0500/0501 performance series electronic pressure switch offers a small compact electronic switch without compromising on quality which comes factory set (unadjustable by the user) with overpressure protection (up to 2x), has a long service life and is also attractively priced especially at high volumes. Using a ceramic sensor in thick film technology for a good operating temperature range and accuracy, there are six standard pressure ranges starting from 0.2 bar all the way up to 0..100 bar and a hysteresis of 1%-98%, available in normally open or normally closed with a PNP transistor output. The wetted parts are made of ceramic, stainless steel and either NBR, EPDM OR FKM ensuring excellent media compatibility, with six standard electrical connection options including Deutsch, DIN and M12 combined with two standard thread type options.



Customer specific solutions are also available on request.

### Application examples

- Automotive
- Braking systems
- Medical
- Mobile hydraulics
- Off highway
- Off-shore
- Rail

Specifications

<b>Accuracy</b>	±0.5 % of adjustment range (Full scale) at room temperature
<b>Adjustment range max</b>	2
<b>Adjustment range min</b>	0
<b>Burst Pressure</b>	8
<b>EMC</b>	EMC 2014/30/EU; EN 61000-6-2:2005; EN 61000-6-3:2007
<b>Hysteresis</b>	1...98% full scale, programmable at factory (maximum tolerance ±1.0% of adjustment range nominal pressure)
<b>IP Class</b>	IP67
<b>Lifespan Mechanical</b>	5,000,000 pulsations at rise rates to 1 bar/ms nominal pressure
<b>Long-Term Stability</b>	±0.1 % of adjustment range (full scale) per year
<b>Max. pressure</b>	4
<b>Output</b>	PNP
<b>Pressure rise</b>	≤ 1 bar/ms
<b>Repeatability &amp; Reproducibility</b>	±0.1 % of adjustment range (full scale)
<b>Supply Voltage DC Max</b>	32
<b>Supply Voltage DC Min</b>	9,6
<b>Switching point adjustment range</b>	2...100 % of adjustment range(full scale), set at factory
<b>Switching time</b>	< 4 ms
<b>Temperature ambient from</b>	-30
<b>Temperature ambient to</b>	100
<b>Temperature range of media from</b>	-30
<b>Temperature range of media to</b>	100
<b>Weight</b>	80



no / nc	
○ 1	(+)
○ 2	(GND)
○ 3	(OUT)

DIN EN 175301-800-A	M 12 - DIN EN 61076-2-001 A	ISO 1570-A1-4.1																														
<table border="1"> <thead> <tr> <th>Pin</th> <th>Assignment</th> </tr> </thead> <tbody> <tr><td>1</td><td>Uv</td></tr> <tr><td>2</td><td>Gnd</td></tr> <tr><td>3</td><td>Uv</td></tr> <tr><td>4</td><td>Uv</td></tr> </tbody> </table>	Pin	Assignment	1	Uv	2	Gnd	3	Uv	4	Uv	<table border="1"> <thead> <tr> <th>Pin</th> <th>Assignment</th> </tr> </thead> <tbody> <tr><td>1</td><td>Uv</td></tr> <tr><td>2</td><td>nc</td></tr> <tr><td>3</td><td>Gnd</td></tr> <tr><td>4</td><td>Uv</td></tr> </tbody> </table>	Pin	Assignment	1	Uv	2	nc	3	Gnd	4	Uv	<table border="1"> <thead> <tr> <th>Pin</th> <th>Assignment</th> </tr> </thead> <tbody> <tr><td>1</td><td>Uv</td></tr> <tr><td>2</td><td>nc</td></tr> <tr><td>3</td><td>Gnd</td></tr> <tr><td>4</td><td>Uv</td></tr> </tbody> </table>	Pin	Assignment	1	Uv	2	nc	3	Gnd	4	Uv
Pin	Assignment																															
1	Uv																															
2	Gnd																															
3	Uv																															
4	Uv																															
Pin	Assignment																															
1	Uv																															
2	nc																															
3	Gnd																															
4	Uv																															
Pin	Assignment																															
1	Uv																															
2	nc																															
3	Gnd																															
4	Uv																															
<ul style="list-style-type: none"> <li>• 50 mm without copper solder</li> <li>• 77 mm with copper solder</li> </ul>	<ul style="list-style-type: none"> <li>• 54 mm</li> </ul>	<ul style="list-style-type: none"> <li>• 56 mm</li> </ul>																														
Order number: 018	Order number: 002	Order number: 004																														
<table border="1"> <thead> <tr> <th>Pin</th> <th>Assignment</th> </tr> </thead> <tbody> <tr><td>1</td><td>Uv</td></tr> <tr><td>2</td><td>Gnd</td></tr> <tr><td>3</td><td>Uv</td></tr> </tbody> </table>	Pin	Assignment	1	Uv	2	Gnd	3	Uv	<table border="1"> <thead> <tr> <th>Pin</th> <th>Assignment</th> </tr> </thead> <tbody> <tr><td>A</td><td>Uv</td></tr> <tr><td>B</td><td>Gnd</td></tr> <tr><td>C</td><td>Uv</td></tr> </tbody> </table>	Pin	Assignment	A	Uv	B	Gnd	C	Uv	<table border="1"> <thead> <tr> <th>Pin</th> <th>Assignment</th> </tr> </thead> <tbody> <tr><td>red</td><td>Uv</td></tr> <tr><td>white</td><td>nc</td></tr> <tr><td>black</td><td>Gnd</td></tr> </tbody> </table>	Pin	Assignment	red	Uv	white	nc	black	Gnd						
Pin	Assignment																															
1	Uv																															
2	Gnd																															
3	Uv																															
Pin	Assignment																															
A	Uv																															
B	Gnd																															
C	Uv																															
Pin	Assignment																															
red	Uv																															
white	nc																															
black	Gnd																															
<ul style="list-style-type: none"> <li>• 61 mm</li> </ul>	<ul style="list-style-type: none"> <li>• 61 mm</li> </ul>	<ul style="list-style-type: none"> <li>• 47 mm (+ 25 mm band width)</li> <li>Cable length: &lt;math&gt;\infty&lt;/math&gt;</li> </ul>																														
Order number: 007	Order number: 010	Order number: 011																														
Thread code: M12	Thread code: M12																															