



## ESI - PR3100 - INDUSTRIAL PRESSURE SENSOR

PR3100-0010AB  
4-20mA, 0..10 bar, G1/4, DIN

- Suitable for the majority of industrial applications
- Reliable pressure measurement
- Long service life
- All stainless steel construction



### Product description

The PR3100 is constructed from stainless steel which incorporates thick film, ceramic and bonded strain gauge technology. This offers excellent stability and accuracy over a long service life. On request this is also available in corrosion resistant materials. The available pressure range options are from 0-1Bar to 0-600Bar.

There are optional ATEX and IECEx approved versions of the PR3100 available for Explosion protection for flammable gases (zone0), dusts (zone 20) and mining areas (group I M1).

### Specifications

<b>Ambient temperature</b>	-20..85°C
<b>EMC</b>	EN61000-6-4, EN61000-6-2
<b>Linearity</b>	≤±0.3% BSFL
<b>Media temperature</b>	-20..85°C
<b>Overpressure protection</b>	20 bar
<b>Pressure Range Max</b>	10
<b>Pressure Range Min</b>	0
<b>Pressure reference</b>	Gauge or Absolute
<b>Sensor technology</b>	Thick film or Bonded foil strain gauge
<b>Storage temperature</b>	5..40°C
<b>Supply voltage</b>	13-36 V DC

