



## SUCO - 0186/0187 PRESSURE SWITCH

Stainless steel body

0186457031003

0,5..5 bar, G1/4, CO, NBR, Spade, Stainless steel

- Up to 250 V
- Spade terminals
- Five adjustment ranges from 0,5..5 bar to 50-200 bar
- Changeover (SPDT)
- Over pressure safety of 300 bar or 600 bar



### Product description

The 0186/0187 series pressure switch is part of the changeover contact range from SUCO. Offering a maximum voltage of 250 V with a normally open and normally closed contact housed in a hex 27 zinc plated body offering a high pressure resistance. The switch point is very stable even after a long period of time and high load and also adjustable on site and can come pre-set.

Common applications include medical, chemical and water applications.

### Specifications

<b>Adjustment range max</b>	5
<b>Adjustment range min</b>	0,5
<b>Approvals</b>	CSA US, RoHS II
<b>Contact load max ac</b>	4
<b>Contact load max dc</b>	0,25
<b>Deviation max</b>	±0,3
<b>Hysteresis</b>	10-30% depending on set value
<b>IP Class</b>	IP00
<b>Lifespan Mechanical</b>	1 million exchanges
<b>Max switching frequency/min</b>	200
<b>Max. pressure</b>	300
<b>Pressure Range Max</b>	5
<b>Pressure Range Min</b>	0,5

Pressure type	Relativt tryck
Temperature ambient from	-20
Temperature ambient to	80
Temperature range of media from	-40
Temperature range of media to	100
Weight	100
Voltage AC / DC Max	250
Voltage AC / DC Min	10

