

KUEBLER - ABSOLUTE-CODED ANGULAR TRANSMITTER SENDIX 5863/5883, OPTICAL, SSI, Ø58 MM SERIE 5863

- Housing diameter Ø58 mm
- SSI / BiSS
- Safety-Lock™
- High enclosure class



Product description

Sendix 5863/5883 is a multivariate sensor with SSI / BiSS interface in robust design. Thanks to the construction of Safety-Lock™ as well as the fully cast housing, the sensor is able to handle even the more demanding applications where there are high demands on the sensor. The wide temperature range combined with the high enclosure class allows the sensor to be used outdoors as well as applications where large temperature changes occur. Sendix 5863/5883 has LED indication which facilitates diagnosis of the sensor and a set button that facilitates calibration.

Please refer to the images below for ordering information.

Order code	8.5863 . XXXXX . XX2X								
Shaft version	Type	a	b	c	d	e	f	g	h
a Flange		d Type of connection				e Code		g Inputs / outputs ⁵⁾	
1 = clamping flange, IP65 ø 58 mm [2.28"]		1 = axial cable, 1 m [3.28'] PVC				B = SSI, binary		2 = SET, DIR input	
3 = clamping flange, IP67 ø 58 mm [2.28"]		A = axial cable, special length PVC *)				C = BiSS, binary		additional	
2 = synchro flange, IP65 ø 58 mm [2.28"]		2 = radial cable, 1 m [3.28'] PVC				G = SSI, gray		status output	
4 = synchro flange, IP67 ø 58 mm [2.28"]		B = radial cable, special length PVC *)				f Resolution ⁵⁾		h Options (service)	
5 = square flange, IP65 □ 63.5 mm [2.5"]		3 = axial M23 connector, 12-pin				A = 10 bit ST + 12 bit MT		1 = no option	
7 = square flange, IP67 □ 63.5 mm [2.5"]		4 = radial M23 connector, 12-pin				1 = 11 bit ST + 12 bit MT		2 = status LED	
6 = servo flange, IP65 ø 63.5 mm [2.5"] ¹⁾		5 = axial M12 connector, 8-pin ⁴⁾				2 = 12 bit ST + 12 bit MT		3 = SET button and	
8 = servo flange, IP67 ø 63.5 mm [2.5"] ¹⁾		6 = radial M12 connector, 8-pin ⁴⁾				3 = 13 bit ST + 12 bit MT		status LED	
b Shaft (ø x L), with flat		*) Available special lengths (connection types A, B):				4 = 14 bit ST + 12 bit MT			
1 = 6 x 10 mm [0.24 x 0.39"] ²⁾		2, 3, 5, 8, 10, 15 m [5.56, 9.84, 16.40, 26.25, 32.80, 49.21']				7 = 17 bit ST + 12 bit MT			
2 = 10 x 20 mm [0.39 x 0.79"] ³⁾		order code expansion .XXXX = length in dm							
3 = 1/4" x 7/8"		ex.: 8.5863.112A.G323.0030 (for cable length 3 m)							
4 = 3/8" x 7/8"		c Interface / power supply		Optional on request					
		1 = SSI, BiSS / 5 V DC		- Ex 2/22 ⁶⁾					
		2 = SSI, BiSS / 10 ... 30 V DC		- other singleturn resolutions					
		3 = SSI, BiSS + 2048 ppr. SinCos / 5 V DC		- surface protection salt spray tested					
		4 = SSI, BiSS + 2048 ppr. SinCos / 10 ... 30 V DC		- seawater resistant (stainless steel V4A)					
		5 = SSI, BiSS / 5 V DC, with sensor output		Salt spray tested / stainless steel V4A as standard types (deliverable as from 1 unit)					
		6 = SSI, BiSS + 2048 ppr. SinCos / 5 V DC, with sensor output		salt spray tested:		V4A			
		7 = SSI, BiSS + 2048 ppr. RS422 (TTL-comp.) / 5 V DC		8.5863.32X6.XX22-C		1.4404		stainless steel V4A:	
		8 = SSI, BiSS + 2048 ppr. RS422 (TTL-comp.) / 10 ... 30 V DC						8.5863.32X6.XX22-V4A	
		9 = SSI, BiSS + 2048 ppr. RS422 (TTL-comp.) / 5 V DC, with sensor output							

