

EARTH TERMINALS - SCREW ON - SL 2.5-35 MM², SSL 50-70MM²

SL, SSL

1056.2

Terminal Block SL 2.5sq Earth

- Screw to rail construction
- SL - Material polyamide 6.6 - UL94-V2
- Temperature resistance -40 °C...+105 °C
- SSL - Material polyamide 6.6 - UL94-V0
- Temperature resistance -40 °C...+120 °C



Product description

The range also includes disconnect terminals, fused terminals, actuator, sensor, motor-connection terminals and a range of direct mount options. For applications where space is at a premium the TS15 range is small and compact, but can still accommodate 4mm² cable sizes

Specifications

| | |
|---|-------------------------------|
| Approvals | UL, cUL, KEMA KUR, NEMKO, EAC |
| Connections | 2 |
| Contamination degree | 3 |
| Country of origin | CZ |
| Cross connect channels | 1 |
| Cross section single wire from | 0,2 |
| Cross section single wire to | 4 |
| Cross section stranded wire from | 0,2 |
| Cross section stranded wire to | 4 |
| Cross section stranded with ferrule from | 0,2 |
| Cross section stranded with ferrule to | 2,5 |
| Cross-Section | 2,5 |
| cUL test standard | C22.2 No 158 |
| EAC test standard | TR ZU 004/2011 |

| | |
|--|-------------------|
| Flammability class | UL94-V2 |
| Height TS 35/7.5 | 47 |
| KEMA KEUR test standard | EN 60947-7-2:2009 |
| Length | 52 |
| Nemko test standard | EN 60947-7-2:2002 |
| Number of levels | 1 |
| Number of test pick off options | 1 |
| Operating temperature from | -40 |
| Operating temperature to | 105 |
| Overvoltage category | III |
| Pack Size | 100 |
| Plug gauge acc. EN 60 947-1 | A3 |
| Rated wire cross section from (AWG) | 22 |
| Rated wire cross section to (AWG) | 12 |
| Screw size | M 2,5 |
| Stripping Length | 10 |
| Tariff code | 85369010 |
| Torque max | 0,8 |
| Torque Min | 0,4 |
| UL test standard | UL 1059 |
| Weight | 17,92 |
| Width | 6 |

