

EARTH TERMINALS - SCREW ON - SL 2.5-35 MM², SSL 50-70MM²

SL, SSL

1056.2

Terminal Block SL 2.5sq Earth

- Screw to rail construction
- SL - Material polyamide 6.6 - UL94-V2
- Temperature resistance -40 °C...+105 °C
- SSL - Material polyamide 6.6 - UL94-V0
- Temperature resistance -40 °C...+120 °C



Product description

The range also includes disconnect terminals, fused terminals, actuator, sensor, motor-connection terminals and a range of direct mount options. For applications where space is at a premium the TS15 range is small and compact, but can still accommodate 4mm² cable sizes

Specifications

Approvals	UL, cUL, KEMA KUR, NEMKO, EAC
Connections	2
Contamination degree	3
Country of origin	CZ
Cross connect channels	1
Cross section single wire from	0,2
Cross section single wire to	4
Cross section stranded wire from	0,2
Cross section stranded wire to	4
Cross section stranded with ferrule from	0,2
Cross section stranded with ferrule to	2,5
Cross-Section	2,5
cUL test standard	C22.2 No 158
EAC test standard	TR ZU 004/2011

Flammability class	UL94-V2
Height TS 35/7.5	47
KEMA KEUR test standard	EN 60947-7-2:2009
Length	52
Nemko test standard	EN 60947-7-2:2002
Number of levels	1
Number of test pick off options	1
Operating temperature from	-40
Operating temperature to	105
Overvoltage category	III
Pack Size	100
Plug gauge acc. EN 60 947-1	A3
Rated wire cross section from (AWG)	22
Rated wire cross section to (AWG)	12
Screw size	M 2,5
Stripping Length	10
Tariff code	85369010
Torque max	0,8
Torque Min	0,4
UL test standard	UL 1059
Weight	17,92
Width	6

