

## DOUBLE DECK TERMINALS - RKD 2.5-4MM<sup>2</sup>

RKD, RKDG

1127.2

Terminal Block RKD 2.5sq Double Deck Beige

- Screw cross connectors
- Temperature resistance -40 °C...+105 °C
- Polyamide 6.6 UL94-V2
- Same level screw option
- Versions with electronic components fitted



### Product description

### Specifications

<b>Approvals</b>	CSA, CSA US, KEMA KUR
<b>Connections</b>	2 x 2
<b>Contamination degree</b>	3
<b>Country of origin</b>	CZ
<b>Cross connect channels</b>	2
<b>Cross section single wire from</b>	0,2
<b>Cross section single wire to</b>	4
<b>Cross section stranded wire from</b>	0,2
<b>Cross section stranded wire to</b>	4
<b>Cross section stranded with ferrule from</b>	0,2
<b>Cross section stranded with ferrule to</b>	2,5
<b>Cross-Section</b>	2,5
<b>CSA test standard</b>	C22.2 No 158
<b>CSAus test standard</b>	UL 1059
<b>Flammability class</b>	UL94-V2
<b>Height TS 35/7.5</b>	56
<b>KEMA KEUR test standard</b>	EN 60947-7-1:2009

<b>Length</b>	60,2
<b>Number of levels</b>	2
<b>Number of test pick off options</b>	1
<b>Operating temperature from</b>	-40
<b>Operating temperature to</b>	105
<b>Overvoltage category</b>	III
<b>Pack Size</b>	100
<b>Plug gauge acc. EN 60 947-1</b>	A3
<b>Rated Current CSA</b>	20
<b>Rated current CSAus</b>	20
<b>Rated Current IEC</b>	24
<b>Rated impulse voltage</b>	6
<b>Rated wire cross section from (AWG)</b>	22
<b>Rated wire cross section to (AWG)</b>	14
<b>Rated voltage CSAus</b>	300
<b>Rated Voltage IEC</b>	500
<b>Screw size</b>	M 2,5
<b>Stripping Length</b>	7
<b>Tariff code</b>	85369010
<b>Torque max</b>	0,8
<b>Torque Min</b>	0,4
<b>Weight</b>	10,84
<b>Width</b>	5
<b>Voltage CSA</b>	300