

EARTH TERMINALS - SCREW ON - SL 2.5-35 MM², SSL 50-70MM²

SL, SSL

1056.2

Terminal Block SL 2.5sq Earth

- Screw to rail construction
- SL - Material polyamide 6.6 - UL94-V2
- Temperature resistance -40 °C...+105 °C
- SSL - Material polyamide 6.6 - UL94-V0
- Temperature resistance -40 °C...+120 °C



Product description

The range also includes disconnect terminals, fused terminals, actuator, sensor, motor-connection terminals and a range of direct mount options. For applications where space is at a premium the TS15 range is small and compact, but can still accommodate 4mm² cable sizes

Specifications

Approvals	UL, cUL, KEMA KUR, NEMKO, EAC
Color	Green/yellow
Connections	2
Contamination degree	3
Country of origin	CZ
Cross connect channels	1
Cross section single wire from	0,2
Cross section single wire to	4
Cross section stranded wire from	0,2
Cross section stranded wire to	4
Cross section stranded with ferrule from	0,2
Cross section stranded with ferrule to	2,5
Cross-Section	2,5
cUL test standard	C22.2 No 158

EAC test standard	TR ZU 004/2011
Flamklass	UL94-V2
Height TS 35/7.5	47
Insulation Material	Polyamide 6.6
KEMA KEUR test standard	EN 60947-7-2:2009
Length	52
Mounting	TS 35
Nemko test standard	EN 60947-7-2:2002
Number of levels	1
Number of test pick off options	1
Operating temperature from	-40
Operating temperature to	105
Overvoltage category	III
Pack Size	100
Plug gauge acc. EN 60 947-1	A3
Rated wire cross section from (AWG)	22
Rated wire cross section to (AWG)	12
Screw size	M 2,5
Screw type	Slotted
Stripping Length	10
Tariff code	85369010
Torque max	0,8
Torque Min	0,4
Type of terminal	Screw Terminals, DIN Rail terminals
UL test standard	UL 1059
Weight	17,92
Width	6

