

TEST-DISCONNECT TERMINALS PTK

1130.2

Terminal Block Test Disconnect PTK 10sq Beige

- Multi-foot TS35/TS32
- Touch-safe to VBG 4
- Dual function, disconnect & test



Product description

CONTA-CLIP test-disconnect terminals are available in the following three basic versions, each with or without a pre-assembled socket plug. All versions provide touch-safe protection according to DGUV-3. A captive, screw-on sliding partition is used to separate the current and voltage paths. The switch position is always easy to detect since the disconnect screw has a yellow insulating sleeve. In all versions, the STB 14/4 socket plugs can be used for a test pick-off for measuring values using the PS 4 test plug or the conventional (4 mm) insulated test plugs. The VH 19 connecting sleeves and the BS 25 screws or STB 14/4 socket plugs are required for fastening the QVS cross-switches above the terminal block. The cross-switches are available from 2 to 4 poles. The QSB internal cross-switches are positioned within the terminal block and make contact over the sliding contact on the LT- or QT-terminals. The cross-switches are available from 2 to 4 poles. The BS 25 mounting screws are used together with the VH 19 connecting sleeves to establish contact with the QVS cross-switches.

Specifications

| | |
|---|-------------|
| Approvals | CSA, CSA US |
| Color | Beige |
| Connections | 2 |
| Contamination degree | 3 |
| Country of origin | DE |
| Cross connect channels | 2 |
| Cross section single wire from | 0,2 |
| Cross section single wire to | 10 |
| Cross section stranded wire from | 0,2 |
| Cross section stranded wire to | 10 |
| Cross section stranded with ferrule from | 0,2 |
| Cross section stranded with ferrule to | 10 |

| | |
|--|-----------------|
| Cross-Section | 10 |
| CSA test standard | C22.2 No 158 |
| CSAus test standard | UL 1059 |
| Flamklass | UL94-V2 |
| Height TS 32 | 51,5 |
| Height TS 35/7.5 | 47 |
| Insulation Material | Polyamide 6.6 |
| Length | 72 |
| Mounting | TS 35 and TS 32 |
| Number of levels | 1 |
| Operating temperature from | -40 |
| Operating temperature to | 105 |
| Overvoltage category | III |
| Pack Size | 50 |
| Plug gauge acc. EN 60 947-1 | A5 |
| Rated Current CSA | 45 |
| Rated current CSAus | 45 |
| Rated Current IEC | 10 |
| Rated impulse voltage | 4 |
| Rated wire cross section from (AWG) | 8 |
| Rated wire cross section to (AWG) | 22 |
| Rated voltage CSAus | 600 |
| Rated Voltage IEC | 400 |
| Screw size | M 4 |
| Screw type | Slotted |
| Stripping Length | 12 |
| Tariff code | 85369010 |
| Torque max | 2 |
| Torque Min | 1,2 |
| Weight | 24,66 |
| Width | 8 |
| Voltage CSA | 600 |

