


SCREW FUSE TERMINALS

SK, STK, STKD, SIK, SSIK

1078.2

Terminal Block STK 4sq Single Deck Fused Beige

- Material polyamide 6.6
- Temperature resistance -40°C...+120°C
- Fire-resistance class V0 - SSIK
- LED indicator
- Pluggable cross connectores - SSIK Range



Product description

Features of the SSIK range Up to 140°C Two cross connect channels for plugin SQI cross connectors Hinged lever with room for spare fuse Optional LED module SSIK4 fuse sizes 5x20, 5x25 and 5x30 SSIK6 fuse sizes 6.3x25 and 6.3x32 Can be used with solid link as a disconnect terminal Two or three disconnect levers can be operated simultaneously by using the VBS connection sleeves Fuse-disconnect terminal STK 1/STK 2 The STK 1 and the STK 2 fuse-disconnect terminals are a low profile and compact shape so they take up minimal space. The hinged lever is used to hold the fuse and locks into its open position. LED status displays are available in a variety of voltage ranges. Features of the STK 1/STK 2 Combi-foot snaps on to TS 35/TS 32 or mounting foot for the TS 15 rail Connection cross-section up to 4 mm² STK1 and STK2 hold fuses (5 x 20/5 x 25) Compact design STK2 - Two or three disconnect levers can be operated simultaneously by using the VBS connection sleeves Can be used with solid link as disconnect terminal Fused terminal SK 1 The SK 1 fused terminals are constructed with a screw cap are designed for 5 x 20 fuses (without indicator) and 5 x 25-sized (with indicator). Fuses are screwed into the fused terminal via the screw cap. Status displays using LEDs, neon indicator lamps are also available for a wide variety of voltage ranges. Features of SK 1 Terminal housing PA 6.6 UL 94-V0 glass-fibre reinforced High continuous-use temperature range Fuses are screwed into the fused terminal via the screw cap Fused terminals are available with status displays for a variety of voltage ranges Fuse disconnect terminal SIK 10/SIK 10/Z This is the old version of fuse-disconnect terminals features a hinged lever that can be locked into its open position for supporting the micro-fuse. Features of the SIK 10/SIK 10/Z Combi-foot can snap on to TS 32/TS 35 rails Connection cross-section up to 10 mm² SIK 10 holds fuses (5 x 20/5 x 25/5 x 30) SIK 10 Z holds fuses (6.3 x 32/6.3 x 25)

Specifications

Approvals	UL, CSA, CSA US, KEMA KUR
Color	Beige
Connections	2
Contamination degree	3
Country of origin	CZ
Cross section single wire from	0,2
Cross section single wire to	4
Cross section stranded wire from	0,2
Cross section stranded wire to	4
Cross section stranded with ferrule from	0,2
Cross section stranded with ferrule to	4

Cross-Section	4
CSA test standard	C22.2 No 158
CSAus test standard	UL 1059
Flamklass	UL94-V2
Fuse max	6,3
Fuse size	5 x 20 / 5 x 25 mm
Height TS 32	39
Height TS 35/7.5	43,5
Insulation Material	Polyamide 6.6
KEMA KEUR test standard	EN 60947-7-1:2009, EN 60947-7-3:2009
Length	51,4
Mounting	TS 35 and TS 32
Number of levels	1
Operating temperature from	-40
Operating temperature to	105
Overvoltage category	III
Pack Size	100
Plug gauge acc. EN 60 947-1	A4
Rated Current CSA	6,3
Rated current CSAus	6,3
Rated Current To UL	16
Rated impulse voltage	4
Rated wire cross section from (AWG)	22
Rated wire cross section to (AWG)	12
Rated voltage CSAus	500
Rated Voltage To UL	600
Screw size	M 3
Screw type	Slotted
Stripping Length	9
Tariff code	85369010
Torque max	1
Torque Min	0,5
Type of terminal	Screw Terminals, DIN Rail terminals
UL test standard	UL 1059

Weight 11,14

Width 8

Voltage CSA 500

