

ADVANCED ILLUMINATION - BL-S050075 EUROBRITE™

Strobe /Continuous Backlight

BL-S050075-470
Ai EuroBrite™ Backlight, Small, Blue 470

- Cost-effective, feature-rich design
- On-board smart driver - seamless strobe or continuous
- Robust, sealed IP67 enclosure
- Easy M12X1 connection



Product description

With complete built in control for continuous and strobe modes, the Eurobrite™ range outdoes the competition in many ways. One major feature of the Eurobrite™ is Adaptive Power™ which utilizes an onboard thermistor to maximize light output in continuous mode. As well as Adaptive Power™ to provide maximal output pulse in strobe mode regardless of the exposure period.


Additional features:

- IP67 sealed enclosure suitable for washdown environments
- Rugged construction that has been tested to withstand over 1000lb
- Industrial grade LEDs providing high-intensity surface illumination of 38klux

For other wavelength options not listed here please [contact us](#).

Specifications

Approvals	IEC 62471, CE, RoHS
Connector/controller	Strobe
IP Class	IP67
Length	75
Operating temperature	0°C - 60°C
Photobiological Risk Factor IEC 6247	Group 1 (low risk)
Standard cable length	No cable included, use standard coded 5-pin M12
Wave-Length	470
Weight	92,53
Width	89



Length (mm)	75
Width (mm)	89
Height (mm)	30

Dimensions are in millimeters.