



## ADVANCED ILLUMINATION - AL46120 - BALA LIGHTING

### 20" Broad Area Linear Array

AL46120-395C5  
Ai BALA Bar Light, 20", UV, pulsar



- Developed to handle a long, wide field with low angle of view
- Very even lighting throughout the area
- Legacy product see AL150

#### Product description

The AL46120 range of BALA (Broad Area Linear Array) bar lights are legacy part number derived from the AL150 range. Designed for applications that require broad illumination over a wide area, or for applications requiring an even broader field of illumination, utilise 2 BALA bar lights in parallel. The AL46120 bar light series is expandable in 1" increments up to 82".

#### Power options include:

- C1 connector - for use with DCS series controllers
- C5 connector - for use with Pulsar 320 strobe controller
- Continuous in-line controller - powered by 24V power supply
- Combination strobe/continuous in-line controller - powered by 24V power supply
- Default-OFF strobe/continuous in-line controller - powered by 24V power supply
- Flying/tinned leads - powered by 24V power supply

#### Other Wavelength options:

- UV - 395
- Blue - 470
- Green - 520
- Red - 625, 660
- Infrared - 880
- White - WHI

For enquiries or quotes for sizes and power options not listed here please [contact us](#).

#### Specifications

<b>Approvals</b>	CE, RoHS, IEC
<b>Color</b>	Ultraviolet
<b>Connector/controller</b>	C5 connector
<b>IP Class</b>	IP50
<b>Length</b>	535
<b>Operating temperature</b>	0 - 60°C
<b>Wave-Length</b>	395
<b>Weight</b>	508,9

