

## ADVANCED ILLUMINATION - BL-S050075 EUROBRITE™

### Strobe /Continuous Backlight

BL-S050075-470  
Ai EuroBrite™ Backlight, Small, Blue 470

- Cost-effective, feature-rich design
- On-board smart driver - seamless strobe or continuous
- Robust, sealed IP67 enclosure
- Easy M12X1 connection



#### Product description

With complete built in control for continuous and strobe modes, the Eurobrite™ range outdoes the competition in many ways. One major feature of the Eurobrite™ is Adaptive Power™ which utilizes an onboard thermistor to maximize light output in continuous mode. As well as Adaptive Power™ to provide maximal output pulse in strobe mode regardless of the exposure period.


#### Additional features:

- IP67 sealed enclosure suitable for washdown environments
- Rugged construction that has been tested to withstand over 1000lb
- Industrial grade LEDs providing high-intensity surface illumination of 38klux

For other wavelength options not listed here please [contact us](#).


#### Specifications

<b>Approvals</b>	IEC 62471, CE, RoHS
<b>Color</b>	Blue
<b>Connector/controller</b>	Strobe
<b>IP Class</b>	IP67
<b>Length</b>	75
<b>Operating temperature</b>	0°C - 60°C
<b>Photobiological Risk Factor IEC 6247</b>	Group 1 (low risk)
<b>Standard cable length</b>	No cable included, use standard coded 5-pin M12
<b>Wave-Length</b>	470
<b>Weight</b>	92,53
<b>Width</b>	89



Length (mm)	75
Width (mm)	89
Height (mm)	30

Dimensions are in millimeters.



Length (mm)	75
Width (mm)	89
Height (mm)	30

Dimensions are in millimeters.