

ASCO - COAXIAL VALVES

SCG287A001



- G3/8 - G1
- Temperature -20 to 100 ° C
- Pressure 0 to 40 bar
- Medium water, oil, gases
- Brass or stainless steel body



Product description

Coaxial valves are used in applications for high pressure and high flows. The coaxial valve can accommodate flow in both directions. Coaxial valves are available in electrically controlled versions and pressure controlled namur versions.

Model SCG287

Function



- Brass/stainless
- 2/2 normally closed/open
- 3/8"-1"
- 0-40 bar
- 37-2,031 l/min.

Model SCG387

Function



- Brass/stainless
- 3/2 normally closed/open
- 3/8"-1"
- 0-40 bar
- 37-203 l/min.

Model G287/Namur

Function



- Brass/stainless
- 2/2 normally closed/open
- 3/8"-1"
- 0-40 bar
- 37-203 l/min.

Model G387/Namur**Function**

- Brass/stainless
- 3/2 normally closed/open
- 3/8"-1"
- 0-40 bar
- 37-203 l/min.

For more information contact OEM Automatic, product area Pressure & Flow and order a separate catalogue.

Specifications

Differential Pressure Air Max	40
Differential Pressure Max	40
Differential Pressure Min	0
Differential Pressure Oil Max	40
Differential Pressure Water Max	40
Flow Max l/min Double	36,6
Temperature range of media from	-20
Temperature range of media to	100
Throughput	10
Voltage AC	230