

## ASCO - 2/2 PULSE VALVE 3/4"-3"

SCG353A043

Solenoid pulse valve 2/2 NC 3/4" 230VAC Thread

- Currentless closed
- Thread or quick coupling
- Electric/air controlled
- Housing in aluminium



### Product description

### Specifications

<b>Coil Material</b>	Epoxy
<b>Connection Thread</b>	3/4 BSP
<b>Differential Pressure Air Max</b>	8,5
<b>Differential Pressure Min</b>	0,35
<b>Flow Factor / Flow Coefficient</b>	14
<b>Flow Max l/min Double</b>	233
<b>Function 1</b>	2/2
<b>Function 2</b>	Normally Closed (SPST)
<b>IP Class</b>	IP65
<b>Material Body</b>	Aluminium
<b>Material of seals</b>	NBR
<b>Material Plunger</b>	Stainless steel
<b>Material Short Call</b>	Copper
<b>Materials Spring</b>	Stainless steel
<b>Max. pressure</b>	10
<b>Membrane Material</b>	TPE

<b>Power Consumption</b>	6
<b>Temperature range from</b>	-20
<b>Temperature range of media from</b>	-20
<b>Temperature range of media to</b>	85
<b>Temperature range to</b>	85
<b>Throughput</b>	25
<b>Weight</b>	0,7
<b>Voltage AC</b>	230