

## ASCO - 2/2 PROPORTIONAL VALVE 1/8"

SCG202A201VS3

Proportional valve 2/2 NC 1/8" 24VDC

- Normally closed
- Compact version
- Working pressure 0 to 8 bar
- Housing in brass or stainless



### Product description

### Specifications

<b>Coil Material</b>	Epoxy
<b>Connection Thread</b>	1/8 BSP
<b>Differential Pressure Air Max</b>	8
<b>Differential Pressure Min</b>	0
<b>Differential Pressure Oil Max</b>	5
<b>Differential pressure vacuum max</b>	1
<b>Differential Pressure Water Max</b>	5
<b>Flow Factor / Flow Coefficient</b>	0,05
<b>Flow Max l/min Double</b>	0,7
<b>Function 1</b>	2/2
<b>Function 2</b>	Normally Closed (SPST)
<b>IP Class</b>	IP65
<b>Material Body</b>	Brass
<b>Material Plunger</b>	Stainless steel
<b>Material Slide Ring</b>	PTFE
<b>Materials Seat</b>	Brass

<b>Materials Seat Seal</b>	FPM
<b>Materials Spring</b>	Stainless steel
<b>Max. pressure</b>	35
<b>Power Consumption</b>	6,3
<b>Sensitivity</b>	<1%
<b>Temperature range from</b>	0
<b>Temperature range of media from</b>	0
<b>Temperature range of media to</b>	50
<b>Temperature range to</b>	40
<b>Throughput</b>	1,2
<b>Weight</b>	0,2
<b>Viscosity Max</b>	50
<b>Voltage DC</b>	24

