

## ASCO - 2/2 PROPORTIONAL VALVE 1/4"

SCG202A001VS3

Proportional valve 2/2 NC 1/4" 24VDC"

- Normally closed
- Compact version
- Working pressure 0 to 16 bar
- Housing in brass or stainless



### Product description

### Specifications

|   |                        |
|---|------------------------|
| <b>Coil Material</b>                    | Epoxy                  |
| <b>Connection Thread</b>                | 1/4 BSP                |
| <b>Differential Pressure Air Max</b>    | 16                     |
| <b>Differential Pressure Min</b>        | 0                      |
| <b>Differential pressure vacuum max</b> | 1                      |
| <b>Flow Factor / Flow Coefficient</b>   | 0,05                   |
| <b>Flow Max l/min Double</b>            | 0,8                    |
| <b>Function 1</b>                       | 2/2                    |
| <b>Function 2</b>                       | Normally Closed (SPST) |
| <b>IP Class</b>                         | IP65                   |
| <b>Material Body</b>                    | Brass                  |
| <b>Material Plunger</b>                 | Stainless steel        |
| <b>Material Slide Ring</b>              | PTFE                   |
| <b>Materials Seat</b>                   | Brass                  |
| <b>Materials Seat Seal</b>              | FPM                    |
| <b>Materials Spring</b>                 | Stainless steel        |

|                                 |     |
|---------------------------------|-----|
| Max. pressure                   | 35  |
| Power Consumption               | 8   |
| Sensitivity                     | <2% |
| Temperature range from          | -10 |
| Temperature range of media from | -10 |
| Temperature range of media to   | 90  |
| Temperature range to            | 75  |
| Throughput                      | 1,2 |
| Weight                          | 0,5 |
| Viscosity Max                   | 21  |
| Voltage DC                      | 24  |

