

ASCO - 2/2 PROPORTIONAL VALVE ANGLE-SEAT VALVE

E290A385PD

- 2/2 normally closed
- Gate signal 0-10 V, 0.20 mA or 4-20 mA
- Working pressure 0 to 16 bar
- Housing in bronze or stainless



Product description

Specifications

Connection Air	1/8 BSP
Connection Thread	3/4 BSP
Current max	0,15
Differential Pressure Air Max	10
Differential Pressure Max	10
Differential Pressure Min	0
Differential Pressure Oil Max	10
Differential Pressure Water Max	10
Differential steam pressure max	10
Disc Material	Brass
Disc Sealing Material	PTFE, Stainless steel
Flow Factor / Flow Coefficient	7,1
Flow Max l/min Double	118
Function 1	2/2
Function 2	Normally Closed (SPST)
IP Class	IP65

Material Body	Bronze
Material of body	Bronze
Material Operator	Reinforced polyamide
Material Rod	Stainless steel
Materials Piston Rod Seal	PTFE
Max. pressure	16
Operating Voltage AC / DC Max	24
Pilot Pressure Max	8
Pilot Pressure Min	4
Power Consumption	3,6
Repeatability	<1 %
Temperature range from	0
Temperature range of media from	-10
Temperature range of media to	180
Temperature range to	50
Throughput	20
Type of valve	Proportional valve
Viscosity Max	600

