

# KUEBLER - WIRE ENCODER D125

SERIE D8.D125

- Measuring range 6 .... 10m
- Integrated inclinometer
- Can be ordered with redundancy
- IP67
- -40 to +85°C



### Product description

Please refer to the images below for ordering information.

Order code with analog sensor		D8 . D125 . XXXX . XXX1 . X 000			
		a	b	c	d
<b>a</b> Measuring length	<b>b</b> Sensor type	<b>c</b> Type of connection			
0600 = 6 m	A22 = 0 ... 10 V <sup>1)</sup>	1 = M12 male connector, 5-pin			
0700 = 7 m	A44 = 0,5 ... 4,5 V	<b>d</b> Power supply			
0800 = 8 m	R22 = 0 ... 10 V, redundant <sup>1)</sup>	1 = 9 ... 30 V DC			
0900 = 9 m	R44 = 0,5 ... 4,5 V, redundant	2 = 5 V DC <sup>2)</sup>			
1000 = 10 m					

Order code with CANopen and inclinometer		D8 . D125 . XXXX . RC11 . 1X 00				
		a	b	c	d	e
<b>a</b> Measuring length	<b>b</b> Sensor type	<b>c</b> Type of connection				<b>e</b> Inclinometers
0600 = 6 m	RC1 = CANopen redundant	1 = M12 male connector, 5-pin				0 = none
0700 = 7 m		<b>d</b> Power supply				1 = 1 inclinometer
0800 = 8 m		1 = 9 ... 30 V DC				2 = 2 inclinometers
0900 = 9 m						
1000 = 10 m						

