## **KUEBLER - MAGNET SENSOR LI50 WITH MAGNETIC TAPE B2**

SERIE 8.LI50

- Resolution up to 0.005 mm
- · Contactless measuring technology
- Status LED
- IP67 Impervious to chips, oil, water, etc.



## Product description

Linear sensor used to measure linear movements with high accuracy, for example in woodworking machines, lathes, material handling, overhead cranes etc. The sensor is almost entirely non-sensitive to chips, oil, dust and water and can thus be used in troublesome environments, it is sealed and has no moving parts. This sensor is fitted to read a magnetic tape with a self-adhesive underside. This sensor is available with different resolutions, and if the recipient (counter/PLC) has a multiplication function, a resolution of 5 µm can be achieved. See electrical data (Resolution, Accuracy) for more information.

Magnetic tape B2 has a polar distance of 5 mm. For the combination LI50/B2, the distance between sensor and tape must be 0.1 to 2.0 mm (1.0 mm is recommended). For the magnet sensor, the slope must not exceed  $\pm 3^{\circ}$ , the rotation must not exceed  $\pm 3^{\circ}$  and the offset must not exceed  $\pm 1$  mm.


The following information is required to select the right combination:

- requirement on accuracy (from 0.1 mm to 0.005 mm)
- the movement's speed (taking into account frequency to subsequent systems and the sensor's max. speed)
- the movement's length (to order the magnetic scale's length = required length of measurement + 1 dm)

Please refer to the images below for ordering information.

Order code sensor head Limes LI50	8. LI 50   .   X   1   X   1   .   2   XXX		
<ul> <li>Model</li> <li>1 = IP67, standard</li> <li>2 = IP68 / IP69k and humidity tested</li> </ul>	Output circuit / power supply  1 = RS422 / 4.8 26 V DC  2 = Push-pull / 4.8 30 V DC	<ul><li>Reference signal</li><li>2 = index periodic</li></ul>	Stock types 8.LI50.1111.2050 8.LI50.1111.2250
acc. to EN 60068-3-38, EN 60068-3-78  • Pulse edge interval	Type of connection 1 = cable. 2 m [6.56'] PUR	Code (resolution) 1) 050 = 25 μm 250 = 5 μm	8.LI50.1121.2050 8.LI50.1121.2250
• Pulse edge interval 1 = standard	1 = cable, 2 m [6.56'] PUR	250 = 5 μm	

Order code magnetic band Limes B2	8.B2 . 10			
<b>3</b> <i>Width</i> 10 = 10 mm	0010 = 1 m 0020 = 2 m 0040 = 4 m 0050 = 5 m	0060 = 6 m 0100 = 10 m 0200 = 20 m	Optional on request - other lengths up to 70 m	Stock types 8.B2.10.010.0020



1 mätområde