

DATALOGIC POWERSCAN PM9501-AR SERIES

PM9501-DAR433RB

PowerScan PM9501, 433 MHz, Auto Range, Display/4-Key, Removable Batt

- Detects 1D and 2D code types
- Reads 1D codes up to 3 mils and 2D codes up to 4 mils
- 40,000+ reads per charge
- Interfaces: Keyboard wedge, RS-232, RS-485, USB



Product description

Specifications

Approvals	RoHS
Battery	Lithium-Ion: 3350 mAh
Charge time	4.5hrs
Dimension (mm)	240 x 108 x 95
Drop resistance	Withstands 50 drops from 2m / 6.5ft to concrete
Humidity	0-95% (Non-Condensing)
Immunity To Ambient Light	Immune to light exposure in offices/facilities and direct exposure to sunlight
Interface	RS-232/RS-485/USB
IP Class	IP65
Light Source	LED
Reading Angle Window	Pitch: +/-80°; Roll (Tilt): +/-180°; Skew (Yaw): +/-60°
Reads per charge	40000
Resolution	4 mils
Temperature range bearing, from	-40
Temperature range bearing, to	70
Temperature range from	-20

Temperature range to	50
Weight	485
Wireless Technology	Datalogic STAR Cordless System