

## DATALOGIC RIDA DBT6400

DBT6400-BK

DBT6400, BT Pocket 2D Area Imager, Black



- Detects 1D/2D code types
- Wide VGA 752 x 480 pixel image sensor
- 3,000+ reads per charge
- Interfaces: USB COM, USB-OEM, USB keyboard



### Product description

### Specifications

<b>1D Code types</b>	Auto discriminates all standard 1D codes
<b>2D Code Types</b>	Aztec Code, China Han Xin Code, Data Matrix, MaxiCode, Micro QR Code, QR Code, Aztec Mesas
<b>Approvals</b>	RoHS
<b>Battery</b>	Lithium-ion 700 mAh
<b>Charge time</b>	2.5 hrs
<b>Color</b>	Black
<b>Dimension (mm)</b>	112.5 x 42.3 x 27.5
<b>Drop resistance</b>	Withstands repeated drops from 5ft onto a concrete surface
<b>Humidity</b>	5-95% (Non-condensing)
<b>Immunity To Ambient Light</b>	0-100,000 lux
<b>Interface</b>	USB COM, USB-OEM, USB keyboard wedge
<b>IP Class</b>	IP50
<b>Kit</b>	No
<b>Light Source</b>	White
<b>Postal Code Types</b>	China Post, KIX Post, Planet Code, Postnet, Royal Mail Code (RM4SCC), UK Postal, Australia Postal, Japan Postal, Canadian Post, Korea Post

<b>Readable code types</b>	1D / Linear Codes, 2D Codes, Postal Codes, Stacked Codes
<b>Reading Angle Window</b>	Pitch: +/-65°; Tilt: up to 360°; Skew: +/-60°
<b>Reads per charge</b>	3000
<b>Resolution</b>	4 mil
<b>Sensor type</b>	Wide VGA: 752 x 480 pixels
<b>Stacked Code Types</b>	EAN/JAN Composites, GS1 Databar Composites, GS1 Databar Expanded Stacked, GS1 Databar Stacked, GS1 Databar Stacked Omnidirectional, Macro PDF, Micro PDF 417, PDF 417, UPC A/E Composites
<b>Temperature range bearing, from</b>	-20
<b>Temperature range bearing, to</b>	70
<b>Temperature range from</b>	0
<b>Temperature range to</b>	50
<b>Weight</b>	85
<b>Wireless</b>	Yes
<b>Wireless Technology</b>	Bluetooth Wireless Technology