



## DATALOGIC POWERSCAN PD9130

PD9130-K2

PowerScan PD9100 RS-232 KIT (Cable CAB-434)

- Detects 1D code types
- Reads up to 2.5 mils codes
- Datalogic's exclusive 3 Green Lights (3GL™)
- Interfaces: RS-232, Keyboard Wedge and USB



### Product description

The PowerScan PD9130 linear imager is a corded device offering state-of-the-art performance in an industrial product. This linear imager introduces Datalogic's new and innovative scanning technology, implementing a green scanning line which has the same definition of a laser beam with all the benefits of a linear imager.

The PD9130 imager features Datalogic's exclusive 3 Green Lights (3GL™) for superior good read feedback. The patented 'Green Spot' technology directly on the code and dual Good Read LEDs on the top of the cap increase visibility at any angle.

The PD9130 imager's mechanics have been developed and tested to withstand extreme environmental conditions, maintaining consistent reading performance without degrading performance or reliability. Its ergonomic enclosure is lightweight and well-balanced to ensure optimal operator comfort during scan-intensive operations.

All models have multi-interface capabilities featuring the most popular interfaces; RS-232, Keyboard Wedge and USB.

### Specifications

---

<b>1D Code types</b>	Code 39, Code 93, Code 128, EAN128, Codabar, Plessey, Code 32, Code 11, MSI, GS1 DataBar linear codes, IATA, Follet 2/5, Code 4, Code 5, Codablock F, UPC/EAN, UPC/EAN P2/P5 add ons, UPC/EAN Coupons, ISBN, Code 39 Full ASCII, Interleaved 2/5, Standard 2/5, Code 39 CIP, Industrial 2/5, Datalogic 2/5
<b>Approvals</b>	RoHS
<b>Color</b>	Black, Yellow
<b>Dimension (mm)</b>	212 x 110 x 74
<b>Drop resistance</b>	Withstands 50 drops from 6.6ft onto concrete surface
<b>Extra Features</b>	Kit includes: Scanner PD9130 and Cable CAB-434
<b>Humidity</b>	0-95% (Non-condensing)
<b>Interface</b>	Keyboard wedge, RS-232, USB
<b>IP Class</b>	IP65
<b>Kit</b>	Yes
<b>Light Source</b>	Green LED
<b>Readable code types</b>	1D / Linear Codes
<b>Reading Angle Window</b>	Pitch: +/-75°; Tilt: +/- 45°; Skew: +/-70°
<b>Resolution</b>	2.5 mils
<b>Temperature range bearing, from</b>	-40
<b>Temperature range bearing, to</b>	70
<b>Temperature range from</b>	-20
<b>Temperature range to</b>	50
<b>Weight</b>	340
<b>Wireless</b>	No