



DATALOGIC DSE04X1 DECODED

DSE0451

Intergrated scan moduke, UART 8-pin zif cable

- Maximum resolution 7.5 mils
- Humidity (Non-Condensing) 5 - 95%
- USB/RS-232/8-pin zif cable interfaces
- Ambient light 0-100,000 lux



Product description

Specifications

1D Code types	Auto discriminates all standard 1D codes
2D Code Types	Aztec Code, China Han Xin Code, Data Matrix, MaxiCode, Micro QR Code, QR Code
Approvals	RoHS
Dimension (mm)	13.65 x 40.1 x 47.86
Humidity	5 - 95% (Non-condensing)
Immunity To Ambient Light	0 - 100,000 lux
Interface	8-pin zif cable
Light Source	Illumination: Steady White LEDs
Output current	<150 mA
Postal Code Types	China Post, IMB, KIX Post, Planet Code, Postnet, Royal Mail Code (RM4SCC), Australia Postal, Japan Postal, Korea Post
Readable code types	1D / Linear Codes, 2D Codes, Postal Codes, Stacked Codes
Reading Angle Window	Pitch: +/-60°; Tilt: +/- 180°; Skew: +/-60°
Resolution	7.5 mils
Sensor type	Wide VGA: 752 x 480 pixels

Stacked Code Types	EAN/JAN Composites, GS1 Databar Composites, GS1 Databar Expanded Stacked, GS1 Databar Stacked, GS1 Databar Stacked Omnidirectional, Macro PDF, Micro PDF 417, PDF 417, UPC A/E Composites
Temperature range bearing, from	-40
Temperature range bearing, to	70
Temperature range from	-20
Temperature range to	55
Weight	20