## **BASLER RACER LINE SCAN CAMERAS**

## GigE & Cameralink Line Cameras

RAL2048-48GM Racer GigE Camera, DR-2K-7 14.3mm CMOS, 2k, Mono

- 2 k to 12 k resolution
- Up to 80 kHz Line Rate
- Monochrome Cameras
- GigE Vison Compatible



## Product description

The Basler Racer Line Scan camera features a slim build of only 56mm, to easily fit into most systems, as well as being able to deliver exceptional performance even under low voltage LED lighting.

The Racer camera range is available in GigE or CameraLink with a range of resolutions from 2k to 12k, with a line rate of up to 80 kHz via camera link and up to 51 kHz via GigE.

This range of Line Scan cameras is particularly suited for applications in, web inspections (film, paper, cotton textiles), sorting and packaging (refuse, postal, foodstuffs) and transport related applications (underfloor, rail, overhead, container inspections).

## Specifications

Approvals	CE, EAC, FCC, GenlCam, GigE Vision, RoHS, UL
Digital Inputs	3
Digital Outputs	2
Height	62
Interface	GigE
IP Class	IP30
Length	36
Lens Barrel	C-mount, F-mount, M42, M58
Line Speed Max	51
Operating temperature	-10°C 60°C
Pixel size	7 x 7
Power Consumption	3
Resolution	2k
Resolution Max	2048 x 1 px
Sensor model	DR-2k-7

Sensor size	14.3 mm
Sensor supplier	Awaiba
Shutter type	Global
Weight	240
Width	56

