


KDS SEAL INSERTS

KDS-DE, KDE-DEG, KDS-DES, KDE-DE-FB

28596.6
KDS-DE 2X5-6 GR

- 1.5mm to 35mm, cable diameters
- Patented 'Wave Cut' technology
- Flat cable versions for KDS-FB
- -40°C to 120°C
- IP66 - UL 94-V0 - Grey, UL 94HB- Black



Product description

Conta-Clip offer a wide range of IP66 seals to suit all applications and cable sizes. The seals are rated to IP66, NEMA12 & NEMA 4X and are ECOLAB® certified, they are available in the standard grey colour or black. The black seals have an operating temperature from -40°C to 120°C, are UV-stabilised and have a high chemical resistance. These are available in the small & large square profile seals only. Single hole inserts can accommodate cables diameters from 1.5mm up to 35mm and there is a selection of 2, 3 and 4 hole variants for cable diameters of 4.5mm to 8mm diameter. The introduction of the compact KDS-FB frame now offers a wide range of rectangular inserts designed for flat cables commonly used in the elevator and lifting industry. These can be combined with the small KDS-DE inserts to provide a round & flat cable entry system. Cone shape and seals for AS interface cables complete the range.

Specifications

Approvals	cUL, UL
Cable Diameter Max	6
Cable Diameter Min	5
Country of origin	DE
cUL test standard	C22.2 No. 14-95
Flammability class	V-0
Height	17,7
IP Class	IP66
Length	20,3
NEMA class	4x
Number of cables	2
Operating temperature from	-40

Operating temperature to	90
Pack Size	10
Tariff code	39259020
UL test standard	UL 508
Weight	6,4
Width	20,3