



I SERIES, PANEL MOUNT BEACON, Ø65, Ø45 AND Ø30MM

Series I

800502313

Beacon LED Steady/Flash Red 230/240v AC/DC

- Ø65, Ø45 and Ø30mm Panel mount beacons
- Strobe, Flashing and Steady LED options
- Wide control voltage range



Product description

The comprehensive M22 built-in signal device series is available in three sizes: 30 mm, 45 mm & 65 mm. The high luminosity and signal effect is seen all around due to the calotte. The beacon is extremely durable and vibration-resistant, with a high degree of protection of IP65 and IP67 for prewired models. The I Series range can come with a demountable plug in terminal or individually prewired. A complete range of LED steady/flashing/strobe and multi colour models for versatile applications in the industry, enclosures, etc. It is maintenance free, offers a low current consumption, long life time, shock and vibration-proof. Multi colour models are also available in 6 LED colours individually selectable. Housing and lenses made of impact resistant polycarbonate, housing colour black or grey.

Specifications

Diameter	30
Flash Frequency	2
Height	60
IP Class	IP65
Nominal current	19
Nominal Supply Voltage	230-240 V AC
Operational Temperature	-25°C ... 60°C
Terminal connection	2,5

IBL / IBM / IBS

La	N	Lb		
X	X		----	FLASHING
X	X	X	—	STEADY

Jumper

