



## I SERIES, PANEL MOUNT BEACON, Ø65, Ø45 AND Ø30MM

### Series I

800502313  
Beacon LED Steady/Flash Red 230/240v AC/DC

- Ø65, Ø45 and Ø30mm Panel mount beacons
- Strobe, Flashing and Steady LED options
- Wide control voltage range



### Product description

The comprehensive M22 built-in signal device series is available in three sizes: 30 mm, 45 mm & 65 mm. The high luminosity and signal effect is seen all around due to the calotte. The beacon is extremely durable and vibration-resistant, with a high degree of protection of IP65 and IP67 for prewired models. The I Series range can come with a demountable plug in terminal or individually prewired. A complete range of LED steady/flashing/strobe and multi colour models for versatile applications in the industry, enclosures, etc. It is maintenance free, offers a low current consumption, long life time, shock and vibration-proof. Multi colour models are also available in 6 LED colours individually selectable. Housing and lenses made of impact resistant polycarbonate, housing colour black or grey.

### Specifications

<b>Diameter</b>	30
<b>Flash Frequency</b>	2
<b>Height</b>	60
<b>IP Class</b>	IP65
<b>Nominal current</b>	19
<b>Nominal Supply Voltage</b>	230-240 V AC
<b>Operational Temperature</b>	-25°C ... 60°C
<b>Terminal connection</b>	2,5

### IBL / IBM / IBS

La	N	Lb		
X	X		----	FLASHING
X	X	X	—	STEADY

Jumper

