



I SERIES, PANEL MOUNT BEACON, Ø65, Ø45 AND Ø30MM

Series I

800502313

Beacon LED Steady/Flash Red 230/240v AC/DC

- Ø65, Ø45 and Ø30mm Panel mount beacons
- Strobe, Flashing and Steady LED options
- Wide control voltage range



Product description

The comprehensive M22 built-in signal device series is available in three sizes: 30 mm, 45 mm & 65 mm. The high luminosity and signal effect is seen all around due to the calotte. The beacon is extremely durable and vibration-resistant, with a high degree of protection of IP65 and IP67 for prewired models. The I Series range can come with a demountable plug in terminal or individually prewired. A complete range of LED steady/flashing/strobe and multi colour models for versatile applications in the industry, enclosures, etc. It is maintenance free, offers a low current consumption, long life time, shock and vibration-proof. Multi colour models are also available in 6 LED colours individually selectable. Housing and lenses made of impact resistant polycarbonate, housing colour black or grey.

Specifications

| | |
|--------------------------------|------------------|
| Color House | Black |
| Color Lens | Red |
| Diameter | 30 |
| Flash Frequency | 2 |
| Height | 60 |
| IP Class | IP65 |
| Light source | LED |
| Light type | Flashing, Steady |
| Mounting | Panel mount |
| Nominal current | 19 |
| Nominal Supply Voltage | 230-240 V AC |
| Operational Temperature | -25°C ... 60°C |

IBL / IBM / IBS

| La | N | Lb | | |
|----|---|----|-----|----------|
| X | X | | --- | FLASHING |
| X | X | X | — | STEADY |

Jumper

