



ELECTRIC ACTI9 DISTRIBUTION BOARDS

RCBO iKQE RCBO 1PPNs 20A C 30mA A-type

SEE120C03

Ikqe Rcbo 1Ppns 20A C 30Ma A-Type

- Endurance between 10000 - 20000 cycles
- 150VAC to 230VAC Ue operational voltage
- 400VAC Ui rated insulation voltage
- 4kV Uimp rated impulse withstand voltage
- 50Hz frequency



Product description

It has an electrical endurance going up to 10000 cycles and a mechanical endurance going up to 20000 cycles. The Ue operational voltage is 150VAC to 230VAC. The Ui rated insulation voltage is 400VAC. The Uimp rated impulse withstand voltage is 4kV. The frequency is 50Hz. It is DIN rail mountable. The width in 9mm pitches is 2. The product color is white (RAL9003). The dimensions are (W) 18mm x (H) 93mm x (D) 70mm. The weight is 136g. It has an IP20 degree of protection (as per IEC/EN 60529 standard) and becomes IP40 once in modular enclosure. The operating temperature is from -25°C to 55°C. The storage temperature is from -30°C to 70°C.

Positive contact indication on toggle (guaranteed on/off indication) Lockable in the ON or OFF position Control type toggle Thermal-magnetic trip unit technology Instantaneous earth-leakage protection time delay Neutral position left Speed of connection of plug-On devices