

## JUNG HYGHSPIN ENGINEERED SERIES

### Hygienic twin screw pump

#### HYGHSPIN ENGINEERED

- Flow 30l/h to 350m<sup>3</sup>/h
- Pressure up to 50 Bar
- Viscosity up to 1,000,000 cSt
- Temperature -10°C to +130°C (180°C)
- Max. particle size 67 mm



#### Product description

The HYGHSPIN Engineered series is created by combining different versions of the HYGHSPIN series, making the Engineered Series a bespoke product. With a HYGHSPIN Engineered, we can supply you with the design and the scope of delivery which you require. A variety of special solutions are possible. Irrespective of whether as a heated version, pumps with vapour locked housing seals, special materials or mobile units complete with control systems, we can jointly create with you the optimal design for your application.

#### Specifications

<b>Flow max m<sup>3</sup>/h Double</b>	350
<b>Material of elastomers</b>	HNBR (Nitrile rubber)
<b>Material of pump house</b>	Stainless steel 316L
<b>Material of seals</b>	SiC/SiC
<b>Materials Terminal</b>	Stainless steel 316L
<b>Max. pressure</b>	50
<b>Particle size max</b>	45
<b>Temperature range from</b>	-10
<b>Temperature range to</b>	180