


## INSULATED BOOTLACE FERRULES 6MM<sup>2</sup> TO 150MM<sup>2</sup>

V30AE000542

Bootlace Ferrules 16.0-12 Ivory (100-Pack)

- Funnel feed-in made of polypropylene.
- Heat resistant up to 120 °C
- For wires from 6...150 mm<sup>2</sup>
- Material: E-Cu/A-Cu, galvanically tin-plated



### Product description

European manufactured, this range ensures a reliable crimp without splitting

### Specifications

<b>Color</b>	Ivory
<b>Conductor tube</b>	Copper alloy
<b>Contact surface</b>	Galvanic tin-plated, shiny
<b>Country of origin</b>	DE
<b>Cross Section Max</b>	16
<b>Diameter of collar</b>	8,8
<b>Diameter of tube</b>	5,8
<b>DIN 46228-1:1992</b>	No
<b>DIN 46228-4:1990</b>	Yes
<b>Length</b>	22
<b>Length of tube</b>	12
<b>Operating temperature from</b>	-5
<b>Operating temperature to</b>	105
<b>Pack Size</b>	100

<b>Plastic collar</b>	Polypropylene-homopolymer
<b>Rated wire cross section to (AWG)</b>	6
<b>Standard</b>	French Standard
<b>Stripping Length</b>	15
<b>Tariff code</b>	85369010
<b>Thickness of collar</b>	0,4
<b>Thickness of tube</b>	0,2
<b>Weight</b>	0,71