

## HONSBERG - CRG SERIES FLOW SWITCH

### Paddle

CRG-025HMS

"Paddle switch 1"" DN25-DN300 0,6-90,8m3

- Switching Range 0,2...165,7 m3/h
- Water (oils and aggressive media available on request)
- Male Thread R1"
- Brass or Stainless Steel Wetted Parts
- Max Pressure 11 bar



#### Product description

Model CRG is a universal flow switch in brass or stainless steel. The same switch can be used for a large number of different pipe dimensions by using one or more paddle lengths. Four different paddle lengths are included.

#### Specifications

<b>Connection</b>	External thread 1 "
<b>Contact Rating Max</b>	15
<b>Deviation max</b>	±15 %
<b>Electrical Connection</b>	PG11
<b>Flow Range Max</b>	165,7
<b>Flow Range Min</b>	0,6
<b>Function</b>	Paddle, micro switch switching
<b>Hysteresis</b>	Depending on the breaking value, however, at least 0.1 l / min
<b>IP Class</b>	IP65
<b>Media</b>	Water, (oil on request)
<b>Pipe dimension max</b>	200
<b>Pipe dimension min</b>	25
<b>Pressure drop</b>	Approx. 0.08 bar at max. flow
<b>Pressure Range Max</b>	11

Temperature range of media to	120
Weight	0,95
Viscosity	1
Voltage AC max	250

