



## ENCLOSURE LIGHTING LED 025 ECOLINE

Ecoline

02540.1-11

Ecoline Panel Lamp 24-48V DC Screw Fixing + Switch

- LED long lifetime
- Externally switched version
- Wide AC/DC voltage range
- Quick connect spring terminals



### Product description

LED025 ECOLINE is available in three different mounting options to suit different applications: Magnetic assembly, which can be mounted very quickly and can be moved around the cabinet if necessary. Screw mounting, for "traditional" mounting. Clip assembly, which is a type of screw mounting, but where the lighting can be angled and also easily moved as needed LED025 ECOLINE has the same luminance as a 95W bulb, but consumes only 5 W. LED025 ECOLINE is available with both 100-240 V AC and 90-110 V DC in one and the same unit, which makes it easy for both purchases and storage.

### Specifications

<b>Approvals</b>	CE, cULus, EAC, RoHS, UL, UL E234324, VDE
<b>Connection</b>	2-pole dual cage clamp
<b>Height</b>	34
<b>Humidity Storage</b>	<90% RH
<b>IP Class</b>	IP20
<b>Length</b>	351
<b>Life span</b>	60,000h at +20°C
<b>Lifespan Electrical</b>	60 000h at +20 °C:ssa (+68 °F)
<b>Luminance</b>	400Lm at 120°
<b>Nominal voltage</b>	24-48 V DC
<b>Operating Humidity</b>	< 90% RH
<b>Operational Temperature</b>	-30°C ... +60°C
<b>Power Consumption</b>	5
<b>Storage temperature</b>	-40°C ... +85°C
<b>Weight</b>	0,2
<b>Width</b>	52
<b>Voltage max</b>	60 V dc

Voltage min

20 V dc

