



ENCLOSURE LIGHTING - SL 025

SL 025

02527.0-00
Panel Lights Magnetic 230v

- Slim casing
- Electronic ballast
- Energy saving lamp
- Low energy fluorescent lamp



Product description

Both a magnetic bracket and IR sensor are available as options. If a magnetic bracket is chosen, installation is very simple and the lamp can be easily moved around in the cabinet to suit each situation. If you would also prefer an IR sensor, it only reacts when the door is opened, even if the door is transparent. Installation is facilitated even more in that a door switch is unnecessary.

Specifications

| | |
|--------------------------------|--|
| Approvals | CE, EAC, GS, RoHS, UL, UL E234324, VDE |
| Connection | 3-pole terminal |
| Flammability class | UL94-V0 |
| Frequenze | 50/60 Hz |
| Height | 40 |
| Humidity Storage | <90% RH |
| IP Class | IP20 |
| Length | 345 |
| Life span | 10,000 Hrs |
| Luminance | 900Lm |
| Nominal voltage | 230 V AC |
| Operating Humidity | < 90% RH |
| Operational Temperature | -20°C ... +50°C |
| Storage temperature | -45°C ... +70°C |

| | |
|--------------------|----------|
| Weight | 0,4 |
| Width | 345 |
| Voltage max | 230 V ac |
| Voltage min | 230 V ac |

